

John Guest® Tubing

Top-of-the-line tubing for customers who demand the best!



John Guest tubing

Part Number	Size	Length	Color	No. / Case
PE-08-BI-0500FN	1/4"	500 (ft)	Natural	2
PE-08-BI-0500FW	1/4"	500 (ft)	White	2
PE-08-BI-0500FE	1/4"	500 (ft)	Black	2
PE-08-BI-0500FB	1/4"	500 (ft)	Blue	2
PE-08-BI-0500FR	1/4"	500 (ft)	Red	2
PE-08-BI-0500FO	1/4"	500 (ft)	Orange	2
PE-08-BI-0500FG	1/4"	500 (ft)	Green	2
PE-08-BI-0500FY	1/4"	500 (ft)	Yellow	2
PE-08-BI-1000FN	1/4"	1000 (ft)	Natural	1
PE-08-BI-1000FW	1/4"	1000 (ft)	White	1
PE-08-BI-1000FE	1/4"	1000 (ft)	Black	1
PE-08-BI-1000FB	1/4"	1000 (ft)	Blue	1
PE-08-BI-1000FR	1/4"	1000 (ft)	Red	1
PE-08-BI-1000FO	1/4"	1000 (ft)	Orange	1
PE-08-BI-1000FG	1/4"	1000 (ft)	Green	1
PE-08-BI-1000FY	1/4"	1000 (ft)	Yellow	1
PE-10-CI-0500FB	5/16"	500 (ft)	Blue	2
PE-12-EI-0500FN	3/8"	500 (ft)	Natural	1
PE-12-EI-0500FW	3/8"	500 (ft)	White	1
PE-12-EI-0500FE	3/8"	500 (ft)	Black	1
PE-12-EI-0500FB	3/8"	500 (ft)	Blue	1
PE-12-EI-0500FR	3/8"	500 (ft)	Red	1
PE-12-EI-0500FO	3/8"	500 (ft)	Orange	1
PE-12-EI-0500FG	3/8"	500 (ft)	Green	1
PE-12-EI-0500FY	3/8"	500 (ft)	Yellow	1
PE-16-GI-0250FE	1/2"	250 (ft)	Black	1
PE-16-GI-0250FN	1/2"	250 (ft)	Natural	1

Miscellaneous

Part Number	Description	No. Per Case
TSNIP	Tube cutter	1
BLADES	Replacement blades	1

Flowmatic® Brand Automatic Shut-Off Valves

The original “dual diaphragm” design, with lifetime warranty!

The original *dual diaphragm* design of Flowmatic’s WQA validated valves provide automatic shut-off to supply line when storage tank reaches 65% of inlet pressure, to potentially save thousands of gallons of water per year. Valves are made using FDA grade, NSF certified materials in choice of models and colors. Comes with a lifetime warranty!

Flowmatic brand shut-off valves

Part Number	Size	Fittings	Color	No. / Case
S2000W	1/8"	Jaco	White	100
S2000B	1/8"	Jaco	Black	100
S2000HCW	1/4"	John Guest	White	40
S2000HCB	1/4"	John Guest	Black	40
S3000W	1/4"	Jaco	White	100
S3000B	1/4"	Jaco	Black	100
S3000HCW	1/4"	John Guest	White	50
S3000HCB	1/4"	John Guest	Black	50



Replacement Diaphragms*

Part Number	Description	No. / Case
DPG3000A	Upper Diaphragm (S2000, 3000)	200
DPG3000B	Lower Diaphragm (S2000, 3000)	100

*Prior purchase required

Waterminders®

Valves provide automatic shut-off, based on gallons filtered.

These unique, patented meter valves provide automatic shut off of a potable water system for filter replacement after a pre-determined quantity of water has been filtered.

Features

- Choice of 1,800 or 3,800 gallon capacity
- Settings in 100 gallon increments
- Accuracy within 10% of setting
- Operating pressures from 15 to 125 psi
- Burst tested to 500 psi
- Assortment of fittings
- Manufactured using NSF listed materials
- Models for gallons or liters



Part Number	Capacity	Fittings	Color	Size	No. / Case
WM2000B	1800 (gals.)*	Jaco	Black	1/4" MNPT	60
WM2000W	1800 (gals.)*	Jaco	White	1/4" MNPT	60
WM3000B	3800 (gals.)*	Jaco	Black	1/4" MNPT	60
WM3000W	3800 (gals.)*	Jaco	White	1/4" MNPT	60
WM3001B	15000 (ltrs.)*	Jaco	Black	1/4" MNPT	60
WM2001B	7000 (ltrs.)*	Jaco	Black	1/4" MNPT	60
WM2000HCW	1800 (gals.)*	J. Guest	White	1/4"	60
WM2000HCB	1800 (gals.)*	J. Guest	Black	1/4"	60

Note: * With dial which may be adjusted in increments of 100 gallons.

Booster, Transfer & Variable Speed Pumps

Self priming diaphragm pumps for a wide range of applications.



To boost pressure and increase performance for residential reverse osmosis systems.

Features

- Fully adjustable outlet pressure control
- Automatic regulation of outlet pressure
- Anti-vibration base plate
- Quiet operation

Booster pumps

Part Number	Transformer	Electrical (Volts)	Fittings	Outlet Pressure	Ship Weight	No. / Case
CDP-6800	Required	115	1/4" J.G.	Adjustable	9 (Lbs)	1
CDP-8800	Required	115	3/8" J.G.	Adjustable	9 (Lbs)	1

Note: Pumps listed above require transformer and pressure switch. (See next page)

Transfer/delivery pumps

Part Number	Flow Range (GPM)	Electrical (Volts)	Fittings	Shut-Off Pressure	Ship Weight	No. / Case
5852-7F12-J604	To 1.4	115*	3/8" J.G.	70 psi	9 (lbs)	1
5852-1E13-J574	To 0.6	115*	3/8" J.G.	70 psi	9 (lbs)	1
5853-1E10-A424	To 0.6	115**	3/8" J.G.	60 psi	9 (lbs)	1

Note: *Comes with power cord. **Requires TACS-114-48 transformer (See next page).

Variable speed pumps (multiple location water transfer, varying psi)

Part Number	Flow Range (GPM)	Electrical (Volts)	Fittings	Shut-Off Pressure	Ship Weight	No. / Case
5853-GB12-V81D	0-1.3	115*	3/8" J.G.	40 psi	9 (lbs)	1
5853-GE12-V81D	0-1.3	115*	3/8" J.G.	60 psi	9 (lbs)	1
5502-IDN2-V77D	0.25-3.0	115*	3/8" Ports*	50 psi	9 (lbs)	1

Note: Comes with power cord. * Ports only. QJS553 (3/8" tube) or QJS554 (1/2" tube) fitting required. (See pump accessories.)



Permeate pump

Part Number	Electrical (Volts)	Fitting	Ship Weight	No. / Case
ERP-1000	Non Elec.	1/4" J.G.	2 (lbs)	1