

Flow-Pro® Pressure Gauges

Full line of stainless steel pressure gauges with brass and stainless fittings.



Side mount models (2-1/2" diameter)

Part Number	Type	PSI	KG	Fitting	Material (Body)	Material (Fittings)	Number Per Case
PG05L25	Glycerin Filled	0-75	0-5	1/4" MNPT	304 SS	Brass	1
PG07L25	Glycerin Filled	0-100	0-7	1/4" MNPT	304 SS	Brass	1
PG15L25	Glycerin Filled	0-200	0-15	1/4" MNPT	304 SS	Brass	1
PG20L25	Glycerin Filled	0-300	0-20	1/4" MNPT	304 SS	Brass	1

Back mount models (2-1/2" diameter)

Part Number	Type	PSI	KG	Fitting	Material (Body)	Material (Fittings)	Number Per Case
PG05B25	Glycerin Filled	0-75	0-5	1/4" MNPT	304 SS	Brass	1
PG07B25	Glycerin Filled	0-100	0-7	1/4" MNPT	304 SS	Brass	1
PG15B25	Glycerin Filled	0-200	0-15	1/4" MNPT	304 SS	Brass	1
PG20B25	Glycerin Filled	0-300	0-20	1/4" MNPT	304 SS	Brass	1

All stainless steel side mount models (2-1/2" diameter)

Part Number	Type	PSI	KG	Fitting	Material (Body)	Material (Fittings)	Number Per Case
PG05L25-SS	Glycerin Filled	0-75	0-5	1/4" MNPT	304 SS	304 SS	1
PG07L25-SS	Glycerin Filled	0-100	0-7	1/4" MNPT	304 SS	304 SS	1
PG15L25-SS	Glycerin Filled	0-200	0-15	1/4" MNPT	304 SS	304 SS	1
PG20L25-SS	Glycerin Filled	0-300	0-20	1/4" MNPT	304 SS	304 SS	1

All stainless steel back mount models (2-1/2" diameter)

Part Number	Type	PSI	KG	Fitting	Material (Body)	Material (Fittings)	Number Per Case
PG05B25-SS	Glycerin Filled	0-75	0-5	1/4" MNPT	304 SS	304 SS	1
PG07B25-SS	Glycerin Filled	0-100	0-7	1/4" MNPT	304 SS	304 SS	1
PG15B25-SS	Glycerin Filled	0-200	0-15	1/4" MNPT	304 SS	304 SS	1
PG20B25-SS	Glycerin Filled	0-300	0-20	1/4" MNPT	304 SS	304 SS	1

Flow Meters

Machined and molded bodies for pipe sizes up to 2".



Features & benefits

- Battery operated
- Sturdy ABS construction
- 6 digit LCD displays up to 4 decimal points
- Measures GPM
- Rated for pressures to 300 psi (20 bar)
- Rated for temperatures to 200°F (93°C)

In-line flow meters (with molded body)

Model Number	Pipe Size (MNPT)	Range (GPM)	Range (LPM)	Material	Max. Pressure	Max. Temp.
FPILDFM-38	3/8"	0.8 - 8	3 - 30	ABS	300 psi	200°F (93°C)
FPILDFM-50	1/2"	2 - 20	7 - 70	ABS	300 psi	200°F (93°C)
FPILDFM-75	3/4"	3 - 30	11 - 110	ABS	300 psi	200°F (93°C)
FPILDFM-100	1"	5 - 50	20 - 200	ABS	300 psi	200°F (93°C)



Features & benefits

- Machined body for added strength
- Sturdy polypropylene construction
- 6 digit LCD displays up to 4 decimal points
- Measures GPM
- Rated for pressures to 300 psi (20 bar)
- Rated for temperatures to 200°F (93°C)

In-line flow meters (with machined body)

Model Number	Pipe Size (MNPT)	Range (GPM)	Range (LPM)	Material Pressure	Max. Temp.	Max.
FPILDFM-150	1-1/2"	10 - 100	40 - 400	PP	300 psi	200°F (93°C)
FPILDFM-200	2"	15 - 150	60 - 600	PP	300 psi	200°F (93°C)

Flow-Pro® Ball Valves

High quality, attractively priced ball valves in stock for immediate shipment.



Flow-Pro white NSF certified PVC ball valves (solvent connection)

Part Number	Pipe Connection	Pipe Size	Material	No. Per Case
FP-PVCBV-50	Solvent	1/2"	PVC	100
FP-PVCBV-75	Solvent	3/4"	PVC	100
FP-PVCBV-100	Solvent	1"	PVC	100
FP-PVCBV-150	Solvent	1-1/2"	PVC	48
FP-PVCBV-200	Solvent	2"	PVC	24



Flow-Pro light grey NSF certified CPVC schedule 80 ball valves (solvent connection)

Part Number	Pipe Connection	Pipe Size	Material	No. Per Case
FP-CPVCBV-50	Solvent	1/2"	CPVC	100
FP-CPVCBV-75	Solvent	3/4"	CPVC	100
FP-CPVCBV-100	Solvent	1"	CPVC	100
FP-CPVCBV-150	Solvent	1-1/2"	CPVC	48
FP-CPVCBV-200	Solvent	2"	CPVC	24



Flow-Pro true union PVC ball valves (with both end connections)

Part Number	Pipe Connection	Pipe Size	Material	No. Per Case
FP-PVCUBV-50	Solvent/Threaded	1/2"	Grey PVC	48
FP-PVCUBV-75	Solvent/Threaded	3/4"	Grey PVC	36
FP-PVCUBV-100	Solvent/Threaded	1"	Grey PVC	24
FP-PVCUBV-150	Solvent/Threaded	1-1/2"	Grey PVC	24
FP-PVCUBV-200	Solvent/Threaded	2"	Grey PVC	12
FP-PVCUBV-300	Solvent/Threaded	3"	Grey PVC	6
FP-PVCUBV-400	Solvent/Threaded	4"	Grey PVC	1



Flow-Pro NSF certified grey PVC schedule 80 unions (solvent connection)

Part Number	Pipe Connection	Pipe Size	Material	No. Per Case
FP-PVCU-50	Solvent	1/2"	PVC	100
FP-PVCU-75	Solvent	3/4"	PVC	100
FP-PVCU-100	Solvent	1"	PVC	100
FP-PVCU-150	Solvent	1-1/2"	PVC	48
FP-PVCU-200	Solvent	2"	PVC	24



Flow-Pro NSF certified forged brass ball valves (full port / socket)

Part Number	Pipe Connection	Pipe Size	Material	No. Per Case
FP-BBVS-50	Socket	1/2"	Forged Brass	100
FP-BBVS-75	Socket	3/4"	Forged Brass	60
FP-BBVS-100	Socket	1"	Forged Brass	36



Flow-Pro forged brass ball valves (full port / threaded)

Part Number	Pipe Connection	Pipe Size	Material	No. Per Case
FP-BBVT-50	FNPT	1/2"	Forged Brass	100
FP-BBVT-75	FNPT	3/4"	Forged Brass	100
FP-BBVT-100	FNPT	1"	Forged Brass	50
FP-BBVT-150	FNPT	1.5"	Forged Brass	20
FP-BBVT-200	FNPT	2"	Forged Brass	20



Flow-Pro 316 stainless steel ball valves (two piece full port / threaded)

Part Number	Pipe Connection	Pipe Size	Material	No. Per Case
FP-SBV-50	FNPT	1/2"	316 SS	80
FP-SBV-75	FNPT	3/4"	316 SS	60
FP-SBV-100	FNPT	1"	316 SS	36
FP-SBV-150	FNPT	1-1/2"	316 SS	12
FP-SBV-200	FNPT	2"	316 SS	8
FP-SBV-300	FNPT	3"	316 SS	1



Flow-Pro in-line PVC check valves (solvent connections)

Part Number	Pipe Connection	Pipe Size	Material	No. Per Case
FP-PCV-50	Solvent	1/2"	PVC	120
FP-PCV-75	Solvent	3/4"	PVC	120
FP-PCV-100	Solvent	1"	PVC	80
FP-PCV-150	Solvent	1-1/2"	PVC	60
FP-PCV-200	Solvent	2"	PVC	40



Flow-Pro bronze pressure relief valves with threaded connections (adjustable 75 to 150 psi)

Part Number	Pipe Connection	Pipe Size	Material	No. Per Case
FP-PRV-50	FNPT	1/2"	Bronze	150
FP-PRV-75	FNPT	3/4"	Bronze	150

Flow-Pro dielectric couplings to prevent electrolysis (galvanized x galvanized)

Part Number	Pipe Connection	Pipe Size	Material	No. Per Case
FP-DFG-50	1/2"	1/2"	Galvanized	1
FP-DFG-75	3/4"	3/4"	Galvanized	1